

## SM-DP+ Simulator

Download and install profiles in non-removable eSIM in a device.

### Overview.

**SM-DP+ Simulator** is essential for anyone in the mobile industry who wants to load eSIM profiles onto GSMA Consumer eSIM devices with non-removable eSIMs, when they do not have access to a real SM-DP+.

Verify that the device, its LPA and the eUICC are interoperable with the eSIM profile.

**SM-DP+ Simulator** supports functions on GSMA ES8+ and ES9+ interfaces. Configure the SM-DP+ Simulator via a simple UI or configure and automate testing via a REST API exactly as you need it.

### How it works.

The tool loads eSIM profiles onto GSMA Consumer eSIM devices via Wi-Fi to verify that the device, its LPA and the eUICC are interoperable with the eSIM profile and associated metadata using custom SM-DP+ certificates and keys or with GSMA SGP.26 test certificates and keys used in SGP.23.

**Fime can help you at any stage of your project lifecycle.**

Define

Design

Deliver

Test



eSIM profile, eSIM and device interoperability testing.

### Key benefits

- Eliminate need to book test time on your real SM-DP+ platform.
- Automate and integrate the test tool with your own test environment using REST API.
- Quickly verify and evaluate interoperability between profiles, handsets and eSIMs.
- Download multiple profiles concurrently on different devices with non-removable eSIM.

### Key features

- Supports the functions on GSMA ES8+ and ES9+ interfaces.
- Create your own test network using DNS server.
- Provides detailed logs for ES9+ (including TLS) and ES8+ for profile download.
- Supports eSIM profile download via Activation Code/ QR code and Default DP+ Address with or without Confirmation Code.
- Use Fime's proprietary mechanism or REST API to load profiles into the tool, schedule profile availability and set retry attempts.

## Libraries.

<b>GSMA interfaces</b>	GSMA's ES8+ interface to download the profile between the SM-DP+ simulator and the eUICC in the device.
	GSMA's ES9+ interface to download the profile between the SM-DP+ simulator and the device LPA via Wi-Fi.
	Does not currently support ES2+ functionality, but may in the future.
	Logging of all TLS and RSP layer traffic on ES8+ and ES9+
<b>Secure channel support</b>	Support for TLS and Protocol for Profile Protection (PfPP) via GSMA's ES9+ interface.
	Support for GSMA's SCP03t via GSMA's ES8+ interface.
<b>TCA Interoperable Profile Format</b>	Support of TCA eUICC Profile Package: Interoperability Functional Requirements specification.

## What's in the box?

### REST API for simulator management.

- Start and stop the simulator.
- Check whether the simulator is running.
- List, add and remove profiles.
- Reset the profile download counter.

### Proprietary profile loading mechanism.

- Manually add profiles and profile metadata using our proprietary mechanism.
- Manage GSMA ES2+ profile ordering via a simple UI.

### DNS Server.

- A DNS Server is provided to specify custom domain name (FQDN) to IP address mapping.

## Technical specifications.

- Load the profile and its associated metadata with your own custom SM-DP+ certificates and keys, or with GSMA SGP.26 test certificates and keys used in SGP.23.
- Support for GSMA SGP.22 Profile Download Initiation (equivalent behavior), Common Mutual Authentication, Profile Download and Installation and Notification procedures related to all profile management activities.
- Customers only need their own laptop hotspot or Wi-Fi router to perform testing.



## Contact

To learn more about how Fime can help your business:

[fime.com](https://fime.com)

[sales@fime.com](mailto:sales@fime.com)

F-T-SMDP-A  
eSIM profile, eSIM and device interoperability testing.

© Fime 2024